



- Multi-directional air flow
- Compact and quiet
- Motorised louvres
- Cooling/heating
- Ultra quiet
- Washable air filter
- Easy-to-use remote controller
- Quick and easy installation
- Condensate lift pump

Incorporating the latest fan technology, these units distribute conditioned air through 2, 3 or 4 sides of the unit. In addition, direction flaps allow air to be directed in either a pre-set or a sweep pattern. An additional advantage of the Fujitsu cassette range is that outside air, as well as conditioned air, can be introduced into the room.



For AUY12L/14L/18L



		Inverter Heat Pump - R410A			
		Indoor	AUY12L	AUY14L	AUY18L
		Outdoor	AOY12L	AOY14L	AOY18L
Up/Down Swing Flaps			✓	✓	✓
Auto Flaps			✓	✓	✓
Auto Shut Flaps			✓	✓	✓
Auto Air Flow Adjustment			✓	✓	✓
Auto Restart			✓	✓	✓
Sleep Timer			✓	✓	✓
Program Timer			✓	✓	✓
Auto-Changeover			✓	✓	✓
Connectable Distributing Duct			✓	✓	✓
Connectable Fresh Air Duct			✓	✓	✓
Washable Panel			✓	✓	✓
Nominal Capacity (kW)	Cooling		3.50	4.00	4.70
	Heating		4.00	4.60	4.80
Moisture Removal	l/h		1.30	1.50	2.00
Dimensions (HxWxD) mm	Inner (Ex. Grille)*		235x580x(580+70)	235x580x(580+70)	235x580x(580+70)
	Outer		650x830x320	650x830x320	650x830x320
Net Weight (kg)	Inner (Ex. Grille)*		18	18	18
	Outer		54	54	54
Room Air Circulation (high) m ³ /h	Inner		550	550	620
	Outer		2800	2800	2800
Power Supply	V-PH-Hz		230 / 1 / 50	230 / 1 / 50	230 / 1 / 50
Power Supply To			Outdoor	Outdoor	Outdoor
Running Current (A)	Cooling		5.10	6.00	7.20
	Heating		6.00	7.10	7.50
Starting Current	A		10	10	10
Fuse Rating	A		15	15	20
Power Consumption (kW)	Cooling		1.16	1.36	1.65
	Heating		1.38	1.63	1.71
Interconnecting Cable			3 + E	3 + E	3 + E
Remote Control Type			Wireless	Wireless	Wireless
Noise Levels (dB(A))	Indoor L/M/H		36 / 39 / 42	36 / 39 / 42	37 / 41 / 44
	Outdoor		49	49	51
Max Pipe Length	m		25	25	25
Max Height Difference	m		15	15	15
Refrigerant Charge	m		10	10	10
Pipe Size (inches)	Gas		3/8 (9.52mm)	1/2 (12.70mm)	1/2 (12.70mm)
	Liquid		1/4 (6.35mm)	1/4 (6.35mm)	1/4 (6.35mm)
Operating Range (°C)	Cooling		10 ~ 43	10 ~ 43	0 ~ 43
	Heating		-10 ~ 24	-10 ~ 24	-10 ~ 24
Refrigerant			R410A	R410A	R410A

Cooling & Heating capacities are based on the following conditions:
Cooling: Indoor Temp.: 27°C DB/19°C WB, Outdoor Temp.: 35°C DB/24°C WB
Heating: Indoor Temp.: 20°C DB, Outdoor Temp.: 7°C DB

Note: Fuse ratings shown are only for information. Any fuses or MCB's installed on-site should be sized in accordance with I.E.E. regulations.

For full installation details please contact your local distributor

*Excludes Grille. Grille dimensions = 35x650x650mm, Grille weight = 2.20kg

Distributed by:



ISO 9001:2008 Certified number: 03 02 00000 - Fujitsu General (Thailand) Co., Ltd.
 ISO 14001:2004 Certified number: 03 02 00000 - Fujitsu General (Thailand) Co., Ltd.
 TUV ISO 9001:2008 Certified number: 03 02 00000 - Fujitsu General (Thailand) Co., Ltd.
 BQI ISO 14001:2004 Certified number: 03 02 00000 - Fujitsu General (Thailand) Co., Ltd.

The company reserves the right to make any variation in specification to the equipment described or to withdraw or replace products without prior notification or public announcement. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form any part of any contract. For full installation details please contact your local distributor.